

EXTERNAL

TEMPOTEST

All Tempotest® fabrics are made in Italy and are designed with an elegant and timeless aesthetic, the hallmark of Italian style. Tempotest fabrics are constructed from premium solution dyed acrylic fibre with outstanding technical features that easily withstand the diverse Australasian climate.

Specific colours and patterns have purposefully been selected to create the Tempotest Premium Collection. This collection reflects Australasian character and blends effortlessly into the environment. The high technical quality and innovative Teflon® Extreme finish of Tempotest ensures continued performance in residential and commercial sun protection and exterior decoration applications.

SPECIFICATIONS:

COMPOSITION:	100% Solution Dyed Acrylic
WARP:	31 ends/cm count Ne 20/2
WEFT:	14 picks/cm count Ne 20/2
ROLL WIDTH:	120cm
ROLL LENGTH:	60m
WEIGHT:	300g/m ²
THICKNESS:	0.56mm
WATER COLUMN:	≥ 350mm
IMPERMEABILITY:	Spray Test 5 (100)
OIL REPELLENT:	5 Degree
COLOURFASTNESS:	7/8-8 degree blue scale 4/5 degree greyscale. Warp: 1600 N
BREAKING LOAD:	Elongation: 28.5% Weft: 860 N
HIGH CLEAN:	Elongation: 29.0% Repellent to normal dirt formation Water and oil repellent